



VACUUM MODEL 50-WAV-5 AIR OPERATED IMMERSION SEPARATOR DUSTLESS SANDING VACUUM

- LOW AIR CONSUMPTION
- STAINLESS STEEL & ALUMINUM
- INTERGRATED IMMERSION SEPARATOR
- HEPA ^{Plus*} FILTRATION 99.995 % @ 0.2 MICRON
- STATIC DISSIPATING ESD SAFE
- RCT REMOVABLE COLLECTION TANK
- 3 YEAR WARRANTY



Explosion Proof / Dust Ignition Proof Air-Operated Pneumatic IMMERSION SEPARATOR DUSTLESS SANDING VACUUM CLEANER

Arslan Dustless Sanding Vacuums are specifically designed to safely vacuum the hazardous dust generated during surface preparation, coating removal and body repair in the automotive industry. Arslan explosion proof/dust ignition proof immersion separator vacuums are designed to safely vacuum explosive, flammable, combustible conductive dusts. Our immersion separator system neutralizes explosive, conductive, combustible dust by submerging it into a neutralizing liquid bath, rendering it inert and eliminating any risk of fire or explosion. These explosion proof vacuums comply with NFPA 484 guidelines and are an effective tool for good housekeeping practise as per OSHA. Compressed Air-Operated Vacuums do not have any electrical components that can overheat and be a source of ignition. Our explosion proof/dust ignition proof vacuums are completely grounded and static dissipating because they are built entirely with non-sparking metals and do not have any painted components so there is no risk of fire or explosion from a spark or static build up.

II 2 GD c IIC T6 (85°C)

Class I, Division 1, Groups A, B, C, and D T6 and Class II, Division 1, Groups E, F, G Hazardous Locations as defined in the National Electric Code (NEC) and NFPA 70
EPL Db and EPL Gb (Equipment Protection Level)

Manufactures & Distributors of Quality Body-Shop Equipment

www.arslanauto.com

1-800-465-8575

ARSLAN AUTOMOTIVE

Features:

- Low Air Consumption
- Stainless Steel construction makes it a solid unit that is easy to clean
- Integrated Immersion Separator
- Drain Valve assembly with level indicator
- Includes Degassing Vent
- Static dissipating ESD safe
- RCT Removable Collection Tank system makes it easy to empty and clean
- Stainless steel storage bin for hose and accessories

Filtration System:

- ESD safe filters
- **HEPA^{Plus}*** Filtration with an efficiency of 99.995% @ 0.2 micron

Specifications:

- Dry Collection Only
- Collection Capacity 5 gallon

Dimensions:

- 24" x 24" x 46" weight : 120 lbs

Air requirements:

- 8 CFM Input Air Flow
- 60 PSI Input Pressure (minimum)
- ½" Air Line Hose

Included:

- Static Dissipating Suction w/ Air Supply hose assembly 20'
- Static Dissipating Airline Hose Connection



Manufactures & Distributors of Quality Body-Shop Equipment

www.arslanauto.com

1-800-465-8575